## PATENT ABSTRACTS OF JAPAN

(11)Publication number:

10-036963

(43)Date of publication of application: 10.02.1998

(51)Int.CI.

C23C 14/34

(21)Application number : 08-193332

(71)Applicant : SONY CORP

(22)Date of filing:

23.07.1996


(72)Inventor: KUDO HISASHI

SUGANO YOSHIHIRO

(54) SPUTTERING DEVICE AND FORMATION OF SOFT MAGNETIC COATING USING THE SAME

(57)Abstract:

PROBLEM TO BE SOLVED: To provide a sputtering device capable of forming soft magnetic coating free from magnetic anisotropy and small in coercive force at the time of forming thin coating film by a sputtering method and to provide a method for forming soft magnetic coating film using this. SOLUTION: This device is provided with a target 5 arranged on a cathode part 3, a substrate 6 arranged opposite to the target 5 and a coating thickness correcting board 7 arranged between the target 5 and the substrate 6, and the coating thickness correcting board 7 has an opening part 7a having a shape by which the distribution of the coating film thickness is considered. Then, the opening part 7a has plural slits partitioned by walls in the approximately orthogonal direction to the substrate face.



## LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]
[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office